


55 Inch Outdoor Digital Kiosks (Super thin)**KEY FEATURES**

A+ LCD IPS panel
 FHD 1920x1080 up to 3840x2160 4K
 Brightness ≥ **2000** nits
 7*24 Hours working unattended

Energy-saving WLED backlight
 Weather-proof, Vandal-proof
 Sunlight readable, Auto-Light sensor,
 Anti-radiation, Anti-electromagnetic,
 Protective: 6-8 mm tempered glass.

Optional:


1. Player alone / Network / Touchscreen
2. Air-cooling≤IP55 / Air-conditioner≥IP65
3. OS: Windows / Android / Linux / None
4. Color Options: Grey, White, Black...

PICTURE**Specification Table:**

Digital Signage Size		55"
Model Number		ST-OK-F55ST
PANELS	Panel Type	A+ LCD IPS Panel 55 inch
	Active Area	1209.6×680.4mm (W*H)
	Aspect Ratio	16:9
	Backlight	Patented LED module + Constant power components
	Resolution	1920x1080 Max to 3140x2160 (4K)
	Display Colors	16.7M / 1.07B
	Brightness	2000+ nits Sunlight-readable
	Contrast Ratio	1400:1
	Visual Angle	178°(H) / 178°(V)
	Response Time	≤ 5ms
	S-System	PAL / NTSC / SECAM
	Life Expectancy	60000 Hours
FUNCTIONS	Operation System	Windows, Android, Linux
	Network	Ethernet, Wi-Fi, 4G, 5G, etc
	Network Protocol	TCP IP/PPPOE/ICMP/DHCP/DNS/FTP/HTTPS
	Audio Format	MP3,WMA,AMR,OGG,AAC,WAV,FLAC,APE
	Video Format	MP4,3GP,MPG,AVI,WMV,FLV,SWF,RMVB,MKV,VOB
	Image Format	JPG,BMP,PNG,TIF,ICO,GIF,TGA
	Supportive	Player Alone, Network, Touch Screen

HARDWARE	Materials	Cold-rolled metal plate + special Outdoor Powder
	Color Options	Silver, Grey, White, Black or customized
	Heat Control	Industrial Air-cooling system Air-conditioner system
	Tempered Glass	6-8 mm (AG, AR or Laminated only in requirement)
	IP Rating	Air-cooling $\leq$ IP55 Air-conditioner $\geq$ IP65
	Speakers	2*10W Stereo
	I/O Connectivity	DP, HDMI, RJ-45, USB, Wi-Fi, 4G/5G
	Dimensions	1990x800x125 MM, Customizable
	N.W / G.W	130KG / 162KG
	Certificates	ISO9001/CCC/CE /FCC/RoHS/IP65
	Accessories	Remote Control, Power Cord, Wires, Key, Rack, Instruction, Approval Certificate, Warranty Card
ENVIRONMENT	Operation Temp	-30°C to 55°C
	Storage Temp	-35°C to 60°C
	Working Humidity	10% to 90%
	Storage Humidity	10% to 90%
POWER	Power Voltage	AC100V-240V (50/60Hz)
	Consumption	400W – 1500W (By heat-control system)
	Standby	$\leq$ 3W
	Power Mode	Manual Automatic Timer-setting On or Off

ILLUMINATION DRAWING



(Dimensions might be adaptable by different enclosures and heat-control systems)

DECLARE:

SUNTUNE SignageHub has the rights for final explanations.

Website: www.suntunesignage.com Hotline: (+86) 188-2025-4103 Email : info@suntunesignage.com

Address : Bldg F10, Gangshen Center, Xinniu Rd, Minzhi Str, Longhua Dist., Shenzhen 518131, Guangdong, China.

55 Inch Outdoor Digital Kiosks (Super thin)