

55+43 Inch Multi-panel Airport Advertising Screens (Double-sided)**KEY FEATURES**

Industrial-grade A+ LCD IPS panel
 43 inch: FHD 1920x1080
 55 inch: FHD 1920x1080 up to 3840x2160
 Brightness:
43 inch ≥ 1500 nits
55 inch ≥ 2500 nits
 7*24 Hours working unattended
 Weather-proof & Vandal-proof enclosure
 Sunlight readable, Auto-Light sensor,
 Anti-reflective and shatter-resistant glass.

Optional:

1. Player alone / Network / Touchscreen
2. Air-cooling≤IP55 / Air-conditioner≥IP65
3. OS: Windows / Android / Linux / None
4. Color Options: Grey, White, Black...

PICTURE**Specification Table:**

Digital Signage Size		Mainly 55 inch, optional with 43 inch
Model Number		ST- AS-F55M43M
PANELS	Panel Type	A+ LCD IPS Panel 55 inch + 43 inch
	Active Area	1209.6×680.4mm (W*H); 941.2x529.3 mm (W*H)
	Aspect Ratio	16:9
	Backlight	Patented LED module + Constant power components
	Resolution	1920x1080 Max to 3140x2160 (4K)
	Display Colors	16.7M / 1.07B
	Brightness	2500+ nits Sunlight-readable
	Contrast Ratio	1200:1
	Visual Angle	178°(H) / 178°(V)
	Response Time	≤ 5ms
	S-System	PAL / NTSC / SECAM
	Life Expectancy	60000 Hours
FUNCTIONS	Operation System	Windows, Android, Linux
	Network	Ethernet, Wi-Fi, 4G/5G, etc
	Network Protocol	TCP IP/PPPOE/ICMP/DHCP/DNS/FTP/HTTPS
	Audio Format	MP3,WMA,AMR,OGG,AAC,WAV,FLAC,APE
	Video Format	MP4,3GP,MPG,AVI,WMV,FLV,SWF,RMVB,MKV,VOB
	Image Format	JPG,BMP,PNG,TIF,ICO,GIF,TGA
	Log Management	Support terminal log and playlist log
	Supportive	Player Alone, Network, Touch Screen

HARDWARE	Materials	Cold-rolled metal plate + special Outdoor Powder
	Color Options	Silver, Grey, White, Black or customized
	Heat Control	Industrial Air-cooling system Air-conditioner system
	Tempered Glass	6-8 mm (AG, AR or Laminated only in requirement)
	IP Rating	Air-cooling≤IP55 Air-conditioner≥IP65
	Speakers	2*10W Stereo
	I/O Connectivity	DP, HDMI, RJ-45, USB, Wi-Fi, 4G/5G
	Dimensions	2200x1200x280 MM, Customizable
	N.W / G.W	180KG / 208KG (For reference)
	Certificates	ISO9001/CCC/CE /FCC/RoHS/IP65
	Accessories	Remote Control, Power Cord, Wires, Key, Rack, Instruction, Approval Certificate, Warranty Card
ENVIRONMENT	Operation Temp	-35°C to 55°C
	Storage Temp	-40°C to 60°C
	Working Humidity	10% to 90%
	Storage Humidity	10% to 90%
POWER	Power Voltage	AC100V-240V (50/60Hz)
	Consumption	1.5kW-2.4kW Due to heat-control system
	Standby	≤3W
	Power Mode	Manual Automatic Timer-setting On or Off

ILLUMINATION DRAWING

(Dimensions might be adaptable by different enclosures and heat-control systems)

DECLARE:

Pictures and Parameters here are for reference only. All referred to physical products.
SUNTUNE SignageHub has the rights for final explanations.

Website: www.suntunesignage.com Hotline: (+86) 188-2025-4103 Email : info@suntunesignage.com

Address : Bldg F10, Gangshen Center, Xinniu Rd, Minzhi Str, Longhua Dist., Shenzhen 518131, Guangdong, China.

55+43 Inch Multi-panel Airport Advertising Screens (Double-sided)