


65 Inch Outdoor Touchscreen Directory

KEY FEATURES	PICTURE
A+ LCD panel 1920x1080 FHD, MAX to 3840x2160 (UHD) Brightness ≥ 2000 nits 7*24 Hours working uninterrupted Energy-saving WLED backlight Weatherproof, Vandal-proof, Dustproof Sun-readable, Auto-light sensor Anti-radiation, Anti-electromagnetic Protective: AR 6mm tempered glass Optional: 1. Plug and Play Network Touchscreen 2. Fan-cooling≤IP55 Air-conditioning≥IP65 3. Linux, Android, Windows 4. Grey, White, Black...Customizable	

Specification Table:

Digital Signage Size		65"
Model Number		ST-ITS-T65TM
PANELS	Panel Type	A+ LCD IPS Panel 65 inch
	Active Area	1428.5×803.5 mm (W*H)
	Aspect Ratio	16:9
	Backlight	Patented LED module + Constant power components
	Resolution	1920x1080; Max to 3840x2160 UHD
	Display Colors	16.7M/1.07B 87% (CIE1931)
	Brightness	2000+ nits Sunlight-readable
	Contrast Ratio	1400:1
	Visual Angle	178°(H) / 178°(V)
	Response Time	≤ 5ms
	S-System	PAL / NTSC / SECAM
	Life Expectancy	60000 Hours
FUNCTIONS	Operation System	Windows, Android, Linux
	Network	Ethernet, Wi-Fi, 4G, 5G, etc
	Network Protocol	TCP IP/PPPOE/ICMP/DHCP/DNS/FTP/HTTPS
	Audio Format	MP3,WMA,AMR,OGG,AAC,WAV,FLAC,APE
	Video Format	MP4,3GP,MPG,AVI,WMV,FLV,SWF,RMVB,MKV,VOB
	Image Format	JPG,BMP,PNG,TIF,ICO,GIF,TGA
	Supportive	Player Alone, Network, Touch Screen

HARDWARE	Materials	Cold-rolled metal plate + special Outdoor Powder
	Color Options	Silver, Grey, White, Black or customized
	Heat Control	Industrial Air-cooling system Air-conditioner system
	Tempered Glass	6-8 mm (AG, AR or Laminated only in requirement)
	IP Rating	Air-cooling $\leq$ IP55 Air-conditioner $\geq$ IP65
	Speakers	2*10W Stereo
	I/O Connectivity	DP, HDMI, RJ-45, USB, Customizable
	Dimensions	1700x270x1515 MM, Customizable
	N.W / G.W	186KG / 227 KG (for Reference)
	Certificates	ISO9001/CCC/CE /FCC/RoHS/IP65
	Accessories	Remote Control, Power Cord, Wires, Key, Rack, Instruction, Approval Certificate, Warranty Card
ENVIRONMENT	Operation Temp	-20°C to 55°C
	Storage Temp	-35°C to 60°C
	Working Humidity	10% to 90%
	Storage Humidity	10% to 90%
POWER	Voltage	AC 100V - 240V
	Consumption	1300W – 1800W (by the heat-control systems)
	Standby	$\leq$ 3W
	Power Mode	Manual Automatic Timer-setting On or Off

ILLUMINATION DRAWING:

(Dimensions might be adaptable by different enclosures and heat-control systems)

DECLARE:

Pictures and Parameters here are for reference only. **SUNTUNE SignageHub has the rights for final explanations.**

