49 Inch Weather-resistant Glass Displays

KEY FEATURES	PICTURE
Industrial-grade A+ LCD panel FHD 1920x1080 Brightness: **2000+** Nits 7*24 Hours working uninterrupted IP-rated enclosure with laminated glass, Smart fan cooling with optional heater, Anti-glare and UV-resistant screen surface, Auto-brightness adjustment, Easy access for maintenance. Optional: 1. Player alone / Network 2. Fan-cooling≤IP55 / Optical bonding≥IP67 3. OS: Windows / Android / Linux 4. Color Options: Grey, White, Black…	

Specification Table：

Digital Signage Size		49”
Model Number		ST-OGW-C49RJ
PANEL	Panel Type	A+ LCD Panel 49 inch
	Active Area	1073.8x604 mm (W*H)
	Aspect Ratio	16:9
	Backlight	Patented LED module + Constant power components
	Resolution	1920x1080
	Display Colors	16.7M
	Brightness	**2000+** nits Sunlight-readable
	Contrast Ratio	1200:1
	Visual Angle	178°(H) / 178°(V)
	Response Time	≤5ms
	S-System	PAL / NTSC / SECAM
	Life Expectancy	60000 Hours
FUNCTIONS	Operation System	Windows, Android, Linux
	Network	Ethernet, Wi-Fi, 4G, 5G, etc
	Network Protocol	TCP IP/PPPOE/ICMP/DHCP/DNS/FTP/HTTPS
	Audio Format	MP3,WMA,AMR,OGG,AAC,WAV,FLAC,APE
	Video Format	MP4,3GP,MPG,AVI,WMV,FLV,SWF,RMVB,MKV,VOB
	Image Format	JPG,BMP,PNG,TIF,ICO,GIF,TGA
	Log Management	Support terminal log and playlist log
	Supportive	Player Alone, Network, Touch Screen

HARDWARE	Materials	Cold-rolled metal plate + special **Outdoor Powder**
	Color Options	Silver, Grey, White, Black or customized
	Heat Control	Industrial Air-cooling system
	Tempered Glass	4-6 mm toughed glass
	IP Rating	Air-cooling≤IP55 | Full lamination≥IP67
	Speakers	2*10W Stereo
	I/O Connectivity	DP, HDMI, RJ-45, USB, SD Card…
	Dimensions	1250x804x240 MM, Customizable
	N.W / G.W	54KG / 86KG (for Reference)
	Certificates	ISO9001/CCC/CE /FCC/RoHS/IP65
	Accessories	Remote Control, Power Cord, Wires, Key, Rack, Instruction, Approval Certificate, Warranty Card
ENVIRONMENT	Operation Temp	-35℃ to 55℃
	Storage Temp	-40℃ to 60℃
	Working Humidity	5% to 95%
	Storage Humidity	5% to 95%
POWER	Voltage	AC 100V - 240V, 50/60Hz
	Watts	400W (Due to heat-control system)
	Standby	≤ 3W
	Power Mode	Manual | Automatic Timer-setting On or Off

ILLUMINATION DIMENSIONS:



(Dimensions might be adaptable by different enclosures and heat-control systems**)**

DECLARE:

Pictures and Parameters here are for reference alone. All referred to physical products.
SUNTUNE SignageHub has the rights for final explanations.

49 Inch Weather-resistant Glass Displays (for Reference)

Website: www.suntunesignage.com Hotline: (+86) 188-2025-4103 Email : info@suntunesignage.com
Address : Bldg F10, Gangshen Center, Xinniu Rd, Minzhi Str, Longhua Dist., Shenzhen 518131, Guangdong, China.